

PRIMARY CORNER DESCRIPTION NW 1/16 Sec. 2

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

G. Robert Lecklider - for: Carl Messing - 6/1959 - M11-31

Set - 1/2" rod in mound of stone.
24" Fir N.82°W., 50.7'
12" Fir S.24°E., 26.3'

L. Ed Monrean - For: Roseburg Resources - 4/2004 - M144-47

Found - 1/2" rod in mound of stone w/BTs
Size indeterminate (24") rotten barkless fir stump
bears N.87°W., (N.82°W.) 51.7' (50.7') with
visible scribe "NW 1/16 S2"
30" (12") Fir, bears S.24°E., 24.7' (26.3') with
healed face.
New - 16" D.Fir bears N.60°W., 42.1' face scribed "NW 1/16
S2 BT"

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2923, surveyed July 2018/March
2020- (DCSO records Vol. 59 Pages 24074)

The NW 1/16 sec. cor. of sec. 2, established by Lecklider, in
June, 1959; perpetuated by Monrean, in 2004; and is accepted
as the cor.; monumented with an iron rod, 1/2" dia., firmly
set, projecting 3" above ground, in a collar of stone, from
which the remains of the bearing trees mkd. by Lecklider
A fir, 40" dia., bears S.21°E., 24.3 ft., with a healed
blaze.
and the remains of a bearing tree mkd. by Monrean
A burnt fir stump, 25" dia., bears N.59°W., 42.2 ft., with
lower portion of a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 16" in the
ground, to bedrock, directly over the iron rod, in a mound of
stone, 3 ft. base, to the top, with brass cap mkd.
NW 1/16 S2
2019
from which a new bearing tree
A fir, 11" dia., bears N.20°E., 31.4 ft mkd. NW 1/16 S2 BT
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at
the base right side-center & each monument established or
remonumented has a magnet deposited in a white plastic case
at the base of the stainless steel post. Alum. Angle iron
driven alongside each monument unless a similar marker was
already in place.

continued next page

1

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 520660

PRIMARY CORNER DESCRIPTION NW 1/16 Sec. 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/8/2021 (Filed 4/12/2022) - C.S. File 67/52-1

Found - 3¼" BLM Brass cap (BLM survey added 10/3/2022)
1/2" rod, Lecklider 1959
46" D.Fir burnt bears S.24°E., 24.3 ft. nail left
side center (rec. 24.7) 1959
D.Fir stump burnt & sawn, 22"x 3 ft. lower half
healed scar N.60°w., 42.1 ft. 2004
New - 24"x2' sawn D.Fir stump N.21°W., 21.5 ft. 4" spike
mag nail top center.
Note - Area burnt 9/2020
Corner on top of cutbank. Small landing at end of
road N.25°W., 175'
Compass decl. 14½°E.
See sketch in file
Lat: 43°20'23.54" N Long: 122°54'27.05" W