

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 10 Page(s) 4184)

Set Cedar post (on rocky side hill) 4 ft. long, 3" sq., 24"
in the ground mkd. ¼ S. on N. & S. faces, from which
A Fir 16" dia., bears N.30°E., 20 lks. dist. mkd. ¼ S BT.
A Fir 14" dia., bears S.65°E., 42 lks. dist. mkd. ¼ S BT.

GLO Survey by Fred Mensch, U.S. Surveyor Under Special
Instructions dated May 25, 1916 - (DCSO records Vol. 10
Page(s) 4289)

Intersect the ¼ sec. cor. established by Deputy Flint in 1882
and reestablished by U.S. Surveyor Collier in 1913, which is
a basalt stone 5x10x8 ins. above ground, firmly set mkd. ¼ on
N. face, from which
A Fir 14" dia., bears S.65°E., 42 lks. dist. mkd. ¼ S BT.
(Orig. tree of Flint survey)
A Fir 40" dia., bears N.4°W., 45 lks. dist. mkd. ¼ S35 BT.

(Note: At this time, (July 27, 1997) in the materials
provided for this project, I cannot find any notes for a 1913
Collier survey that re-establishes this corner. V.Laugen)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
July 1967 - C.S. File 54/40-25

Found - No trace of Corner stone nor SE. BT. Call of 26
lks. on bluff 15 ft. high on line, fits good.
Orig. 40" now 40" Fir snag, 20 ft. high, N.4°W.,
29.7 ft. shows "¼ S35 BT" on burned unhealed
blaze. (Mkd. by Collier in 1913)

Set Brass cap at cor. in mound of stone, mkd:

County Surveyors Office

¼ $\frac{S\ 35}{S\ 2}$ T26S R2W
T27S

1967

New BTs- 6" D.Fir N.63°W., 9.2 ft. mkd. ¼ S35 CS BT.

9" D.Fir S.11°W., 3.3 ft. mkd. ¼ S2 CS BT.

Cor. lies on very steep E. slope approx. 225 ft. W. of creek

Survey by Ronald Geisler - For: Champion International -
Mar/April 1984 - M 90-55

Found - 1967 DCSO brass cap/iron pipe.
40" Fir snag, 20 ft. tall, bears N.4°W., 29.7 ft.
(Orig. BT.)

(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5" Fir, down and decaying, bears N.63°W., 9.2 ft.,
scribing visible on open face.
12" Fir bears S.11°W., 3.1 ft. with closed face.
New BT - 6" Fir bears N.38°W., 40.8 ft. scribed ¼ S35 BT.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold,
Cadastral Surveyors & Robert H. Browning, Survey Technician,
under Group No. 1638, surveyed July 1992/April 1995 - (DCSO
records Vol. 51 (Page(s) 19744-5)

The ¼ sec. cor. of secs. 2 and 35, perpetuated by Tracy, in
1967, and further perpetuated by Geisler, in 1984, monumented
with an iron post, 1½" dia., firmly set, projecting 14" above
the ground, in a mound of stone 4 ft. base, 1 ft. high, with
brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by Collier and
reported by Mensch

A decayed fir snag, 36" dia., bears N.4°W., 45 lks., with
scribe marks 1/4 S35 BT visible on an opened blaze.
and a bearing tree mkd. by Tracy

A fir, 16" dia., bears S.18°W., 5 lks., with a healed
blaze.

and a bearing tree mkd. by Geisler

A fir, 9" dia., bears N.33¾°W., 62 lks., with a healed
double blaze.