

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 26 only

Alias	Description

GLO survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4226)

-----

Set sandstone 6x10x15", 10" in the ground for ¼ sec. cor. marked ¼ on N face, from which  
A cedar, 18" dia., bears N.48°W., 21 lks., mkd: ¼ S26 BT.  
A fir, 30" dia., bears S.18°E., 35 lks., mkd: ¼ S35 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4308)

-----

Set an iron post, 3 ft long, 1" dia., 26" in the ground, for ¼ cor. of sec. 26 only, with brass cap mkd: ¼ S26  
1916

from which  
A laurel, 6" dia., bears N.56°E., 24 lks., mkd: ¼ S26 BT.  
A cedar, 50" dia., bears N.42°W., 23 lks., mkd: ¼ S26 BT.  
The cor. established by Deputy Gibb in 1909 as the ¼ cor. of secs. 26 & 35, which is a granite stone, 5x10x6" above ground, firmly set, marked & witnessed as described by the surveyor general, bears N.0°20'E., 18.72 ch.  
I destroy the cor. set in the rejected revision survey as the ¼ cor. of secs. 26 & 35, and marks on BTs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - July 1967 - C.S. File 54/40-29

-----

Found - 1916 GLO brass cap, firmly set & mkd "S¼ S26" under S side of 26" Fir long which we notch around brass cap.  
50" now 66" cedar, alive N.42°W., 15.2 ft. shows scar.  
Laurel stool bears N.56°E., 15.8 ft. locus of NE OBT

New BTs- 16" cedar N.55°W., 38.2 ft. mkd: ¼ S26 CS BT  
26" cedar N.52°E., 43.3 ft. mkd: ¼ S26 CS BT

Note - This corner lies on southerly slope at SW corner of timber in old logged-off unit.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19748)

-----

The ¼ sec. cor. of sec. 26 only, perpetuated by Tracy, in 1967, and utilized by Shrum, in 1981; monumented with an iron post, 1" dia., firmly set, projecting 12" cont. next pg

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 26 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

above the ground, with brass cap (properly)mkd.  
from which the remains of bearing trees mkd. by Mensch  
    A madrone root crown, size indeterminate, bears N.56°E.,  
    24 lks., no marks visible.  
    A cedar, 56" dia., bears N.42°W., 23 lks., with a healed  
    blaze.  
and bearing trees mkd. by Tracy  
    A cedar, 30" dia. bears N.52°E., 65 lks. with scribe marks  
    ¼ S26 CS BT visible on a partially healed double blaze.  
    A cedar, 23" dia., bears N.55°W., 58 lks., with a healed  
    double blaze.

---

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral  
Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 -  
(DCSO records Vol. 58 Page(s) 22937)

-----

The ¼ sec. cor. of sec. 26 only, monumented with an iron  
post, 1" dia., firmly set, projecting 7" above ground, with  
brass cap (properly) mkd.  
from which an original bearing tree  
    A cedar, 62" dia., bears N.42°W., 15.2 ft., with a healed  
    blaze.  
and BTs mkd. by the Douglas County Surveyor's Office in 1967  
    A cedar, 34" dia., bears N.54½°E., 42.9 ft., with a healed  
    blaze. (Record, N.52°E.)  
    A cedar, 32" dia., bears N.55°W., 38.3 ft., with a healed  
    blaze