

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 540240

PRIMARY CORNER DESCRIPTION Center ¼ Cor. Sec. 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T.E. Shrum, Jr - For: Champion Int. - Sept. 15, 1981 - M89-28  
-----  
Set - 2½" alum. cap on a 1"x36" IP (1981) C¼ SEC 26.  
4" D.Fir, bears N.21°30'W., 6.5 ft.  
20" R.Cedar, bears S.55°W., 32.8 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22938)  
-----  
The center ¼ sec. cor. of sec. 26, established by Shrum, in 1981, and is accepted as the cor.; monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with an aluminum cap mkd. SEC 26  
C ¼  
T26S R2W  
LS 1706  
1981  
from which bearing trees mkd. by Shrum  
A fir, 19" dia., bears S.55°W., 31.6 ft., with a healed blaze.  
A cedar, 23" dia., bears N.16¼°W., 6.4 ft., with scribe marks ¼ S26 BT visible on partially healed blaze.  
Corner is located 10 ft. E. of a creek, 2 ft. wide, course N.10°E.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 8/29/2023 - C.S. File 67/56-63  
-----  
Found - 2½" alum cap (properly mkd) on ¾" ID iron pipe up 8" Burned broken 25"x30 ft. R.Cedar\* snag S.55°W., 31.6 ft. blazed burned out.  
Singed 28" D.Fir\* N.16¼°W., 6.3 ft. (rec. 6.4 ft) fully healed single blaze.  
\*Note: tree species were reversed.  
New - 11" burned, dead hemlock N.67°E., 20.4 ft., 3½" mag nail, right side center.  
13" burned, dead D.Fir S.51°E., 16.0 ft., 3½" mag nail, right side center.  
Note - Area burnt 9/2020  
Compass decl. 14½°E.  
Mon. is in burned old growth near bottom of steep draw approx 175 North from abandoned Forest road.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 161563.500 E 278497.990