

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4200)

Set hemlock post, 3 ft. long, & 3" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 S on N face, from which:

- A fir, 12" dia., bears S.50°E., 17 lks., mkd: 1/4 S BT.
- A fir, 12" dia., bears N.20°W., 15 lks., mkd: 1/4 S BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4306)

Intersect the 1/4 sec. cor., established by McQuinn in 1883 and re-established by U. S. Surveyor Collier in 1913*, which is a basalt stone, 5x8x8", above ground firmly set, marked 1/4 on N face, from which

- A fir, 18" dia., bears S.59°E., 17 lks. Marked 1/4 S23 BT (Orig. BT)
- A fir, 18" dia., bears N.15°W., 15 lks. Marked 1/4 S14 BT (Orig. BT)

*Note - (I can not find any record of Collier's resurvey 10/11/2007 DCSO JC)

BLM dependent resurvey by G. Steven Popken, Cadastral Surveyor, Group No. 871, surveyed June/Sept. 1975 - (DCSO Vol. 46 Page(s) 15725-6)

The 1/4 sec. cor. of secs. 14 & 23, determined at record bearing & distance, from the remains of the orig. BTs:

- A root hole, bears S.59°E., 17 lks., with a down fir alongside, 20" dia., with scribe marks 1/4 S23 BT visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

T26S R2W
1/4 S 14
S 23
1975

from which new BTs

- A fir, 13" dia., bears N.4°W., 57 lks., mkd: 1/4 S14 BT.
- A fir, 14" dia., bears S.56°W., 97 1/2 lks., mkd: 1/4 S23 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 1/19/2023 - C.S. File 67/55-31

Found - 3 3/4" brass cap (properly mkd) on 2" iron pipe, up 6".
Continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Sawn 24"x1' D.Fir stump N.4°W., 37.5 ft. to 3½" mag nail set top center.
Tipped out sawn 30"x8' D.Fir stump S.56°W., 64.4 ft. to root hole.
Line tree burned dead 13" Fir ≈ South.
New - Singed 20" I.Cedar N.57°E., 47.5 ft, not blazed or scribed, 3½" mag nail right side center.
Singed 13" I.Cedar S.75°E., 45.8 ft., not blazed or scribed 3½" mag nail right side center.
Sawn 13"x1½ ft. D.Fir stump N.59½°W., 41.0 ft., 3½" mag nail top center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Lat: 43°17'57.26" N Long: 122°54'12.43" W