

PRIMARY CORNER DESCRIPTION 1/4 Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4202)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:
A fir, 10" dia., bears N.21°E., 37 lks., mkd: ¼ S BT.
A fir, 12" dia., bears S.11°E., 14 lks., mkd: ¼ S BT.

BLM dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #664, surveyed April 1968 - (DCSO records Vol. 34 Page(s) 14276)

Point for the ¼ sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:
T26S R2W
¼ S 11
 S 14
 1968

from which
A madrone, 5" dia., bears N.25°E., 80 lks., mkd: ¼ S11 BT.
A fir, 28" dia., bears S.31½°W., 43 lks., mkd: ¼ S14 BT.
The corner falls at the SE cor. of logged area.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19758)

The ¼ sec. cor. of secs. 11 & 14, monumented with an iron post, 2½" dia., firmly set in a mound of stone, 3 ft. base, 1 ft. high, with brass cap (properly) mkd.
from which bearing trees mkd. by Roseberry
A madrone, 11" dia. bears N.25°E. 80 lks with healed blaze
A fir, 36" dia., bears S.31½°W., 43 lks. with healed blaze