

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 540540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bruce Rogers - For: Hult Lumber Co. - July 9, 1969 - M38-25

Set - 1" x 48" I. Rod at center.
New - 8" Alder S.32°E., 17.4 ft. scribed "CS ¼ S11 BT"
 20" cedar N.6°E., 41.7 ft. scribed "CS ¼ S11 BT"

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold,
Cadastral Surveyors & Robert H. Browning, Survey Technician,
under Group No. 1638, surveyed July 1992/April 1995 - (DCSO
records Vol. 51 (Page(s) 19759)

The center ¼ sec. cor. of sec. 11, established by Rogers, in
1969, and is accepted as the corner; monumented with an iron
rod, 1" dia., firmly set, projecting 18". above ground, from
which bearing trees mkd. by Rogers:
 An alder, 12" dia., bears S.31½°E., 25 lks., with decayed
 blaze.
 A cedar, 27" dia., bears N.5¼°W., 63½ lks., with healed
 blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the
ground, with brass cap mkd. T26S R2W
 C 1/4 S 11
 1992
Deposit a white "DEEP-1" magnetic marker at base and iron rod
inside of stainless steel post.