

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 540640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Report sent in by William J. Brayton notes dated June 19, 1952 - Filed July 23, 1953 - C.S. File 41/181

South 20 chs from 1/4 cor. sec. 35, T25-2 & sec. 2, T26-2, set post, thence south 20 chs,
Set - 4" cedar with a:
 46" fir bearing N.45°W., 32.5 ft.
 10" fir bearing S.48°W., 26.5 ft.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24068)

Point for the center ¼ sec. cor. of sec. 2, at intersection with the E. and W. center line.
Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.
 T 26 S R 2 W
 C ¼ S 2
 2019

from which new bearing trees
 A fir, 4" dia., bears S.4°E., 8.2 ft., mkd. X BT.
 A fir, 7" dia., bears S.68¼°W., 16.4 ft., mkd. C¼ S2 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument unless a similar marker was already in place.