

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 35 only

Alias	Description

GLO survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4226)

Set sandstone 6x10x15", 10" in the ground for ¼ sec. cor. marked ¼ on N face, from which
A cedar, 18" dia., bears N.48°W., 21 lks., mkd: ¼ S26 BT.
A fir, 30" dia., bears S.18°E., 35 lks., mkd: ¼ S35 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4308)

The cor. established by Deputy Gibb in 1909 as the ¼ cor. of secs. 26 & 35, which is a granite stone, 5x10x6" above ground, firmly set, marked & witnessed as described by the surveyor general, bears N.0°20'E., 18.72 ch.
I destroy the cor. set in the rejected revision survey as the ¼ cor. of secs. 26 & 35, and marks on BTs.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19747-8)

Point for the ¼ sec. cor. of sec. 35 only.
Set a stainless steel post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd.
T26S R2W
1/4 S 35
1992

from which
A madrone, 14" dia., bears S.37¾°E., 53 lks. mkd. ¼ S35 BT
A fir, 5" dia., bears S.49½°W., 51 lks., mkd. X BT.
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

1