

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 547144

PRIMARY CORNER DESCRIPTION (SE) Corner No. 4 Tract 38

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4343)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for cor. No. 4 of Tract 38, with brass cap mark
TR38 | T26S
4 | R2W
S35
1918
from which
A cedar, 14" dia., bears N.8°W., 31 lks., mkd: 4 TR 38 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - July 1967 - C.S. File 54/40-31

Found - 1918 GLO brass cap, firmly set.
14", now 16" cedar, alive, N.8°W., 20.5 ft., prev. opened & scribe visible "4 TR 38 BT" on decaying blaze.
New BTs- 14" cedar N.26°W., 52.3 ft. mkd. "4 TR 38 CS BT"
10" W.Fir S.16°E., 29.1 ft. mkd. "4 TR 38 CS BT"
Note - This corner lies on very gentle, southeast slope.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19757)

Corner No. 4 of Tract 38, perpetuated by Tracy, in 1967; monumented with an iron post, 1" dia., firmly set, projecting 3 ins. above the ground, with brass cap mkd.
TR 38 | T26S
4 | R2W
S 35
1918
from which the original bearing tree
A cedar, 17" dia., bears N.8°W., 31 lks., with scribe marks TR 38 visible on a partially healed blaze.
and bearing tree mkd. by Tracy
A cedar, 19" dia., bears N.26°W., 79 lks., with scribe marks TR38 CS BT visible on a partially healed blaze.
and a new bearing tree
A fir, 9" dia., bears S.10°W., 20 lks., mkd. S35 BT.
continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 547144

PRIMARY CORNER DESCRIPTION (SE) Corner No. 4 Tract 38

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The corner is located on a gentle S. slope 50 lks. W. of a graveled road 30 lks. wide, bears N. 20° E. and S. 20° W.

(NAD 1927 - from map) Latitude 43°15'52.69"N
(NAD 1927 - from map) Longitude 122°54'02.46"W

From this corner, National Geological Survey triangulation station "SHIVIGNY", 1953, bears N.66°23'30"W., 81.860 chs. (mean bearing and sea level dist.); monumented with a brass disk, 3" dia., set in a concrete post, 10" square, projecting 4" above the ground, mkd. NATIONAL GEOLOGICAL SURVEY SHIVIGNY 1953 1977 and a triangle.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/10/2022 - C.S. File 67/55-6

Found - 2½" GLO brass cap on 1" I.D. iron pipe set flush with ground (properly mkd)
Shattered to ground Cedar stump N.8°W., 20.5 ft. GLO
Burnt-down Cedar N.26°W., 52.1 ft. DCSO
Live 16" W.Fir S.6°W., 13.2 ft. fully healed single blaze (Rec. S.10°W.) BLM
New - Burnt-sawn 18"x3' Cedar stump N.20°W., 25.8 ft. 3½" mag nail top center.
Burnt-sawn 18"x1' Fir stump N.70°E., 53.6 ft. 3½" mag nail top center.
50" D.Fir with line crossing tag S.55°E., 57 ft.
Note - Monument is on flat bench 25 ft west of gravel road.
Area burnt 9/2020
Compass decl. 14½°E.
Lat: 43°15'52.18"N Long: 122°54'06.72"W.