

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 547200

PRIMARY CORNER DESCRIPTION (NE) Corner No. 1 Tract 38

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4341)

-----  
I commence at a point on N bdy. of sec. 35, 40.00 chs. E of the closing cor. of secs. 34 & 35  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for cor. No. 1 of Tract 38, with brass cap marked

T26S R2W  
-----  
S26  
1 | S35  
TR 38 |  
1916

from which

A fir, 40" dia., bears S.60°W., 6 lks. mkd 1 TR 38 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - July 1967 - C.S. File 54/40-30

-----  
Corner No. 1, of Tract 38.

Found - 1918 GLO Brass Cap, firmly set in mound of stone.  
Orig. 40, now Fir, S.60°W. 4.0 ft. Alive, shows good scar.

Since Mensch only marked one BT, we mark new one:  
14" D.Fir S.52°E. 44.0 ft. mkd "1 TR 38 CS BT"

Note - This corner lies approx. 457 ft E of cor. of sec. 26

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19755)

-----  
Cor. No. 1 of Tract 38, on line bet. secs. 26 and 35, perpetuated by Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 1" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which the original bearing tree

A fir, 55" dia., bears S. 60° W., 6 lks., with a healed blaze.

and a bearing tree mkd. by Tracy

A fir, 20" dia., bears S.52°E., 67 lks., with a healed double blaze.