

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4187)

Set post, 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 25, 26, 35, & 36, mkd T26S S25 on NE, R2W S36 on SE, S35 on SW & S26 on NW faces with 1 notch on S & E edges, from which

- A laurel, 6" dia., bears N.15°E., 14 lks., mkd: T26S R2W S25 BT.
- A laurel, 5" dia., bears S.51°E., 26 lks., mkd: T26S R2W S36 BT.
- A laurel, 18" dia., bears S.40°W., 35 lks., mkd: T26S R2W S35 BT.
- A laurel, 5" dia., bears N.52°W., 18 lks., mkd: T26S R2W S26 BT.

GLO survey by Wm. N. Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4225-6)

Intersect N & S line, 16.16 ohs. N of cor. secs. 25, 26, 35 & 36 which is a stake marked as described by the Surveyor General.

Note; As this does not close within limits I retrace my own work without finding error.

At point of intersection

Set granite stone, 6x10x15", 10", in the ground for closing cor. secs. 26 & 35, marked C C on W face with 5 grooves on N & 1 groove on S face, from which

- A laurel, 5" dia., bears S.42°W., 20 lks., mkd: T26S R2W S35 BT.
- A fir, 8" dia. bears N.62°W., 30 lks. mkd: T26S R2W S26 BT

I destroy marking on old cor. referring to secs. 26 & 35.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4291 & 4294-5)

Page 4291

...North, retracing line bet. secs. 35 & 36; at 33.70 chs. fall 25 lks. W of cor. of secs. 25, 26, 35, & 36.

Page 4294-5

Intersect the original cor. of secs. 25, 26, 35 & 36 established by Deputy McQuinn in 1883, reported by Deputy Gibb in 1909, as found by him, but not reestablished. The cor. point is now marked by a granite stone 20x15x12", properly marked, continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

cont... evidently set in place of the old post, fragments of which are found. The position of the tree described in the field notes as the SW bearing tree does not agree with the field notes, as it is the NW. quadrant and is marked for sec. 26. The decayed trunk of the NE bearing tree is found, with marks still legible. Its former position, as shown by the decayed stump, agrees with the field notes. The SE and SW bearing trees are not found. I perpetuate this cor., as follows: At the exact cor. point
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 25, 26, 35 & 36, with bras cap marked

T26S R2W
S 26 | S 25
S 35 | S 36
1916

from which

- A laurel, 6" dia., bears N.85°E., 15 lks., mkd: T26S R2W S25 BT.
- A fir, 6" dia. bears S.12°E., 35 lks. mkd: T26S R2W S36 BT
- A fir, 8" dia. bears S.38°W., 35 lks. mkd: T26S R2W S35 BT
- A laurel, 18" dia., bears N.55°W., 38 lks., mkd: T26S R2W S26 BT.

From this cor. the cor. established by Deputy Gibb in 1909 as the closing cor. of secs. 26 & 35, on the W bdy. of sec. 25, which is a granite stone, 5x10x6" above ground, firmly set, marked & witnessed as described by the surveyor general, bears N.1°51'W., 20.19 chs.

I destroy the corresponding cor. of rejected revision survey & marks on BTS.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - July 1967 - C.S. File 54/40-28

Found - 1916 GLO Brass Cap, firmly set & properly marked. Orig. 18? now 22" Laurel N.55°W. 25.1 ft. Alive, hollow, by looking inside, reverse scribing visible.

- New BTs- 15" D.Fir S.30°E., 16.4 ft. mkd. T26S R2W S36 CS BT.
- 12" D.Fir S.66°W., 25.7 ft. mkd. T26S R2W S35 CS BT.
- 11" Laurel N.35°W., 55.1 ft. mkd. T26S R2W S26 CS BT
- 10" Maple N.72°E., 28.6 ft. mkd. T26S R2W S25 CS BT.

Note - This corner lies on precp. S. E. slope.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19747)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From the cor. of secs. 25, 26, 35 and 36,, monumented with an iron post, 2" diam., firmly set, projecting 16" above the ground, with brass cap (properly) mkd.
from which the remains of a BT mkd. by Mensch in 1916
A madrone stump, 22" dia., bears N.55°W., 38 lks., with fragmentary reverse scribe marks visible through a hollow center.
and BTs mkd. by Tracy
A maple, 10" dia., bears N.72°E., 41 lks., with fragmentary scribe marks on a partially healed blaze.
A fir, 19" dia., bears S.30°E., 25 lks., with a healed blaze.
A fir, 11" dia., bears S.66°W., 38 lks., with a healed blaze.
No suitable bearing trees available in NW. quadrant.

Fd. BC & 3 BTs, set 6' steel post 2' south - by D. Edwards, 3/2008 - M155-16

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22921)

The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2" dia., loosely set, projecting 20" above ground, with brass cap (properly) mkd.
from which the remains of a bearing tree mkd. by Mensch
A sawed, hollow madrone stump, 28" dia., bears N.55°W., 25.1 ft., with no marks visible.
and BTs mkd. by the Douglas County Surveyor's Office in 1967
A maple, 12" dia., bears N.72°E., 27.1 ft., with fragmentary raised scribe marks protruding through a healed blaze.
A fir, 24" dia., bears S.30°E., 16.5 ft., with a healed double blaze.
A fir, 13" dia., bears S.66°W., 25.1 ft., with a healed double blaze.
and a new bearing tree
A cedar, 5" dia., bears N.45°W., 32.3 ft., mkd. X BT.
Raise a mound of stone, 3 ft. base, to top.
A search was made for all original line trees bet. secs. 25 and 26 and none were recovered.

Fd. as per M155-16 10/2015 - By D. Edwards, M169-80