

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by G. Steven Popken, Cadastral, Group No. 871, surveyed June/Sept. 1975 - (DCSO Vol. 46 Page(s) 15720-1)

The ¼ sec. cor. of secs. 23 & 24, monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which the orig. BTs

A fir, 51" dia., bears N.47°E., 6 lks., with healed blaze. (Record, N.50°E.)

A maple, 13" dia., bears S.38°W., 31½ lks., w/scribe marks S23 BT visible on open decayed blaze. (Rec 30 lks.) and bearing trees mkd. by Tracy in 1967

A cedar, 10" dia., bears S.2°E., 46 lks. with scribe marks ¼ S24 CS BT visible on open double blaze.

A hemlock, 10" dia., bears N.64½°W., 41 lks., with scribe marks ¼ S23 CS BT visible on open double blaze.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22924)

The ¼ sec. cor. of secs. 23 and 24, monumented with an iron post, 1" dia., firmly set, projecting 9" above ground, with a brass cap (properly) mkd. from which the original bearing trees

A fir, 58" dia., bears N.47°E., 4.0 ft., with a healed blaze.

A maple, 15" dia., bears S.38°W., 20.8 ft., with no marks visible on a hollow double blaze. and the BTs mkd. by the Douglas Co. Surveyor's Office in 1967

A cedar, 16" dia., bears S.2°E., 30.4 ft., with a healed double blaze.

A hemlock, 13" dia., bears N.64½°W., 27.1 ft., with a healed double blaze.