

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4191)

Set fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 13, 14, 23 & 24, mkd T26S S13 on NE, R2W S24 on SE, S23 on SW & S14 on NW faces with 3 notches on S and 1 notch on E edges, from which
A fir, 24" dia. bears N.25°E., 68 lks mkd: T26S R2W S13 BT
A fir, 20" dia. bears S.20°E., 29 lks mkd: T26S R2W S24 BT
A fir, 20" dia. bears S.75°W., 78 lks mkd: T26S R2W S23 BT
A fir, 25" dia. bears N.20°W., 83 lks mkd: T26S R2W S14 BT

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4292 & 4300-1)

Page 4292
... north... at 85.49 chs fall 1.89 chs. W of cor. of secs. 13, 14, 23, & 24
Pages 4300-1
Intersect the cor, of secs. 13, 14, 23 & 24, established by Deputy McQuinn in 1883. The old post has been replaced at proper point by a basalt stone, 10x10x6" above ground, firmly set, marked with 3 notches on S and 1 notch on E edge; witnessed as described by the surveyor general.
This cor. was also used as a cor. for the rejected revision survey.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy - Cletis Putnam - Oct. 1961 - C.S. File 52/77-6

Found - Mound of rocks & rotten fir stump N.25°E., 44.9 ft., scribing vis.
Fir tree, now 36" S.20°E., 19.1 ft. shows 2 good axe scars. Tree in good condition, did not open.
Remains of rotten Fir stump S.75°W., 51.5 ft. no scribing found.
No trace fd of NW BT location for tree falls in road
Set - Brass cap mkd: County Surveyors T26S R2W S 14 | S 13
Office 1961 S 23 | S 24
Pile stones up around BC.
New BTs- 15" D.Fir S.83°W., 34.3 ft. mkd: T26S R2W S23 CS BT.
6" W.Oak N.84½°W. 24.1 ft. mkd: T26S R2W S14 CS BT.
7" W.Oak S.70°E. 22.0 ft. mkd: T26S R2W S24 CS BT.
No trees available to NE.

Fd. Ok by V. Tracy 7/20/1967 C.S. 54/40-21 cont next pg

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by G. Steven Popken, Cadastral, Group No. 871, surveyed June/Sept. 1975 - (DCSO Vol. 46 Page 15721)

The cor. of secs. 13, 14, 23, & 24, perpetuated & recorded by Godfrey, in 1961, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, alongside of which is a basalt stone, 10x10x6". The brass cap is (properly) mkd., from which the remains of the orig. BTs

A sawed & decayed fir stump, 30" dia., bears N.25°E., 68 lks. no marks visible.

A fir, 35" dia., bears S.20°E., 29 lks., w/healed blaze. and bearing trees mkd. by Godfrey

A W.Oak, 10" dia., bears S.70°E., 33½ lks., w/healed double blaze.

A fir, 17" dia., bears S.81°W., 53 lks., with healed double blaze.

A W.Oak, 7" dia., bears N.86½°W., 37 lks., with healed double blaze. and a new bearing tree

A cedar, 5" dia., bears N.66°E., 49½ lks., mkd. X BT.

Douglas Co. Surveyors Office - Randall Smith - Stephen J. Flause - 12/19/1984 - C.S. File 62/21-11

Found - 1961 DCSO disk on a I.P. protruding 6" above a 2 ft. mound of stone properly marked. 1961

20" now a 30" D.Fir with a double well healed blaze bears S.20°E., 21.1 ft. (Rec. 19.1 ft. is to face of blaze.) (orig.)

24" now a 38" dia. 1 ft. high decayed fir stump, no scribing or blazes fd bears N.25°E. 44.9 ft (orig)

No other orig BTs found.

15" now 20" D.Fir with well healed double blaze bears S.81°W., 33.7 ft. (Rec. S.83°W., 34.3 ft. per 1961 renewal is a slope measurement to face of blaze. (Rec. dist. 35.0 ft. per 1975 BLM resurvey) 1961

6" now 7" W.Oak with a well healed double blaze bears N.86½°W., 23.4 ft. (Rec. N.84½°W. 24.1 ft. per 1961 dist. is a slope measurement to face of blaze.) (Rec. dist. 24.4 ft. per 1975 BLM resurvey) 1961

7" now a 10" W.Oak with a well healed double blaze bears S.70°E., 22.0 ft. 1961

5" now a 7" cedar with a partially healed double blaze scribe "X BT" bears N.66°E., 32.7 ft. per 1975 BLM resurvey.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>No new monument or accessories set. Corner lies approx 100 ft. North of boundary road.</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3-23-2022 (Filed 4/18/2022) - C.S. File 67/52-24 -----</p> <p>Found - DCS0 brass cap Burned, sawn, 32"x6' Fir stump S.20°E., 21.1 ft., healed double blaze. 1883 26" D.Fir S.81°W., 33.7 ft healed double blaze. 1961 Burnt 9" W.Oak N.86½°W., 23.4 ft. healed double blaze. 1961 Burnt, sawn 12"x7' W.Oak stump S.70°E., 22.0 ft. healed double blaze. 1961 Sawn 16"x6½ ft. Cedar stump N.66°E., 32.7 ft., healed double blaze, scribe X BT. 1975 Burnt away, roothole only, N.25°E., 44.9 ft 1883 OBT</p> <p>Note - Area Burnt 9/2020 Compass decl. 14½°E. Corner is approx. 100' N of Boundary Road. See sketch in file</p> <p>Lat: 43°17'58.21" N Long: 122°53'35.46" W</p>
<p>BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCS0 records Vol. 59 Pages 24049) -----</p> <p>The cor. of secs. 13, 14, 23, & 24, reported by Popken in 1975, monumented with an iron post, 1¼" dia. (Rec. 1" dia.), firmly set, projecting 4" above ground, in a mound of stone, 2 ft. base, to the top, with a brass cap (properly) mkd from which the bearing trees reported by Popken</p> <ul style="list-style-type: none">A cedar, 14" dia., bears N.66°E., 32.7 ft., with a healed blaze.An oak, 11" dia., bears S.70°E., 22.1 ft., with a healed double blaze.A fir, 41" dia., bears S.20°E., 19.1 ft., with a healed blaze. (Original)A fir, 20" dia., bears S.81°W., 35.0 ft., with a healed double blaze.An oak, 8" dia., bears N.86½°W., 24.4 ft., with a healed double blaze. <p>Corner is located N., 75 ft., of Boundary Road, graveled surface, 14 ft. wide, bears S.80°E. and N.75°W. NAD 1983 (2011) Latitude: 43°17'58.20" N. Longitude: 122°53'35.43" W.</p>
<p>3</p>