

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24050)

The ¼ sec. cor. of secs. 13 and 14, reported by Roseberry in 1968, monumented with an iron post, 1¼" dia. (Record, 1" dia.), firmly set, projecting 28" above ground, in a mound of stone, 3 ft. base, 24" high, with a brass cap (properly) mkd. from which the remains of the BTs reported by Roseberry

A decayed fir stump, 20" dia., bears N.16°E., 46.5 ft., no marks visible. (Original)

An oak, 8" dia., bears N.66°E., 36.3 ft., with a healed double blaze.

A decayed fir snag, 40" dia., bears N.44½°W., 39.6 ft., with scribe marks CS and other illegible scribe marks visible on partially healed double blaze. (Original) and a new bearing tree

A madrone, 9" dia., bears N.30¼°W., 33.8 ft., mkd. ¼ S14 BT on bark.

Corner is located on top of a large rock outcropping.