TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4195)

Set post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which
A fir, 5" dia., bears S.60°E., 15 lks., mkd: ¼ S BT.
A maple, 5" dia., bears S.65°W., 36 lks., mkd: ¼ S BT.

BLM dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #664, surveyed April 1968 - (DCSO records Vol. 34 Page(s) 14274)

Point for the ¼ sec. cor. of secs. 11 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap marked: T26S R2W

¼
S 11|S 12
1968

from which
A fir, 16" dia., bears S.64°E., 43 lks., mkd: ¼ S12 BT.
A fir, 16" dia., bears S.64°W., 19 lks., mkd: ¼ S11 BT.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19745)

The ¼ sec. cor. of secs. 11 & 12, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap mkd. T26S R2W

¼
S 11|S 12
1968

from which bearing trees mkd. by Roseberry
A fir, 23" dia. bears S.64°E., 43 lks. with a healed blaze
A fir, 23" dia. bears S.64°W., 19 lks. with a healed blaze

Ken Hoffine - For: Lone Rock Timber Co. - 10/1999 - M 133-59

Found - 1968 BLM brass cap
26" D.Fir bears S.64°W., 12.8 ft. (rec. S.64°W. 12.54 ft.) well healed face & BLM tag.
26" D.Fir bears S.64½°E., 28.3 ft. (rec. S.64°E., 28.38 ft.) well healed face & BLM tag.
Corner lies on West edge of bench that lies below extremely steep West slope.