

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4195-6)

-----

Set post, 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 1, 2, 11, & 12, mkd T26S S1 on NE, R2W S12 on SE, S11 on SW & S2 on NW faces with 5 notches on S and 1 notch on E edges, from which

- A fir, 24" dia. bears N.50°E., 80 lks. mkd: T26S R2W S1 BT
- A fir, 36" dia. bears S.60°E., 40 lks mkd: T26S R2W S12 BT
- A fir, 36" dia. bears S.61°W., 48 lks mkd: T26S R2W S11 BT
- A fir, 30" dia. bears N.62°W., 75 lks. mkd: T26S R2W S2 BT

G. Robert Lecklider - For: Mrs. Carl A. Messing - July 6, 1959 - M11-31

-----

Found - 50" Fir, N.50°E., 80 lks.  
46" Fir, S.60°E., 40 lks.

Set - 4"x4' Post &  
14" Fir, S.12°E., 6.0 ft.  
26" Fir, N.51°E., 9.0 ft.  
8" Fir, S.60°W., 10.1 ft.  
6" Fir, N.25°W., 16.7 ft.

BLM dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #664, surveyed April 1968 - (DCSO records Vol. 34 Page(s) 14274-5)

-----

The cor. of secs. 1, 2, 11, & 12, perpetuated & recorded by Lecklider, in 1959, monumented with a fir post, 3" dia., protruding 4 ft. above the ground, firmly set, from which the original BTs:

- A fir, 52" dia., bears N.58°E., 83 lks., with faint original bark scribing visible. (Rec. N.50°E., 80 lks.)
- A fir snag, 48" dia., bears S.65½°E., 44 lks., with faint orig. bark scribing visible & rescribed BT on bark blaze. (Record, S.60°E., 40 lks.)

and bearing trees mkd. by Lecklider in 1959,

- A fir, 27" dia., bears N.47°E., 13½ lks., mkd. S1 R4079 on bark blaze and with healed blaze at base.
- A fir, 10" dia., bears S.18½°E., 9 lks., with a pitched over double blaze.
- A fir, 10" dia., bears S.56½°W., 15½ lks., with scribe marks S11 RE4079 BT visible on partially healed double blaze.
- A fir, 8" dia., bears N.30¼°W., 25 lks., with scribe marks S2 RE4079 BT visible on partially healed double blaze.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
brass cap mkd.

T26S R2W  
S 2 | S 1  
S 11 | S 12  
1968

Reset the wooden post alongside the iron post.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Survey Technician, under Group No. 1638, surveyed July 1992/April 1995 - (DCSO records Vol. 51 (Page(s) 19746-7)

-----  
The cor. of secs. 1, 2, 11, & 12, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir, 52" dia., bears N.58°E., 83 lks., with fragmentary bark scribe marks visible.

A fir snag, 48" dia., bears S.65½°E., 44 lks., with fragmentary bark scribe marks visible.

and the remains of bearing trees mkd. by Lecklider, in 1959, reported by Roseberry

A fir, 30" dia., bears N.47°E., 13½ lks., with bark scribe marks S1 R 4079 visible and a healed blaze.

A fir, 19" dia., bears S.18½°E., 9 lks., with healed double blaze.

A fir, 11" dia., bears S.56½°W., 15½ lks., with healed double blaze.

A fir, 9" dia., bears N.30¼°W., 25 lks., with healed double blaze.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24050-1)

-----  
The cor. of secs. 1, 2, 11, and 12, reported by Bedell, Seibold, and Browning in 1992-95, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.

from which the remains of the bearing trees reported by Bedell, Seibold, and Browning

A fir, 32" dia., bears N.47°E., 8.9 ft., with scribe marks S1 RE 4079 visible on bark and a healed double blaze.

A fir snag, 50" dia., bears N.58°E., 54.8 ft., with a healed blaze. (Original)

A decayed fir snag, 42" dia., bears S.65½°E., 29.0 ft., with scribe marks BT visible on bark. (Original) Cont.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 24" dia., bears S.18½°E., 5.9 ft., with a healed double blaze.  
A fir, 11" dia., bears S.56½°W., 10.2 ft., with a healed double blaze.  
A fir, 10" dia., bears N.30¼°W., 16.5 ft., with a healed double blaze.