TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4197-8)

Set post, 3" sq. 3 ft. long 24" in the ground for ¼ sec. cor. mkd ¼ S on W face, from which
A fir, 18" dia., bears N.22°E., 18 lks., mkd: ¼ S BT.
A fir, 5" dia., bears S.34°W., 61 lks., mkd: ¼ S BT.

G. Robert Lecklider - For: Mrs. Carl A. Messing - July 6, 1959 - M11-31

Set - l½" Pipe in Mound of Stone
36" Fir, N.86°W., 9.2 ft.
6" Fir, S.70°E., 13.2 ft.
Original Corner Not Found.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24051-2)

The ¼ sec. cor. of secs. 1 and 2, reestablished by proportionate measurement by Lecklider, in June 1959. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron pipe, 1 7/8" dia., firmly set, projecting 19" above ground, in a mound of stone, 3 ft. base, 12" high, from which the BTs mkd. by Lecklider
A fir, 13" dia., bears S.71¾°E., 11.5 ft., with a healed blaze.
A fir, 49" dia., bears N.84°W., 9.2 ft., with a healed double blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, in a mound of stone, 3 ft. base, to the top, with brass cap mkd.

T 26 S R 2 W
¼ S2 | S 1
2019

Bury the iron pipe, 32 ins. long, alongside the cor.
Each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument unless a similar marker was already in place.