

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4188)

-----

Set post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which

A laurel, 5" dia., bears N.20°E., 32 lks., mkd: ¼ S BT.

A laurel, 6" dia., bears S.20°W., 15 lks., mkd: ¼ S BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4291 & 4295-6)

-----

Page 4291  
Retracing the line bet. secs. 25 & 36; at 41.79 chs. the ¼ sec. cor. bears North 72 lks.

Page 4295-6  
Intersect the original sec. cor., established by Deputy McQuinn in 1883 & not reported found in any subsequent survey. The old post is found, broken off at the ground. The BTs agree with the field notes in size & kind, but not exactly in position. The original BT on North is dead. I perpetuate this cor. as follows: at the exact cor. point

Set an iron post, 3 ft. long, 1" dia., 26" in th ground, for sec. cor. with brass cap marked

$\frac{1}{4} \frac{25}{36}$   
 1916

from which

A laurel, 10" dia., bears N.24°E., 18 lks., mkd: ¼ S25 BT.

A laurel, 6" dia., bears S.9°W., 11 lks., mkd: ¼ S36 BT.

I destroy the corresponding cor. of the rejected revision survey and marks on BTs.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug. 1967 - C.S. File 54/40-63

-----

Found - 1916 GLO Brass Cap, properly marked.  
 Orig. 10", now 13' Laurel N.24°E. 11.9 ft., alive, scribe marks visible on nearly healed blaze.  
 1916 SW BT gone, only shattered stump remains.

New BTs- 8" D.Fir N.6°E., 4.4 ft. mkd. ¼ S25 CS BT.  
 8" D.Fir S.7°W., 14.9 ft. mkd. ¼ S36 CS BT.

Note - This corner lies on westerly slope approx. 60 ft. W. of top of spur, ridge sloping SW Sec. 36 cut off many years ago.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Seneca Jones Timber Co. - 10/2015 - M169-80

-----

Found - 1916 GLO brass cap  
1916 BT A 16" Madrone bears N.24°E., 11.9 ft.  
1967 DCS BT A 13" Fir bears N.6°E., 4.4 ft.  
1967 DCS BT A 20" Fir bears S.7°W., 14.9 ft.  
All with healed blazes.  
Set - 6 ft. steel post 2 ft. east.