

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4196-7)

Set post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S on N face, from which
A fir, 6" dia., bears N.32½°E., 21 lks., mkd: ¼ S BT.
A fir, 10" dia., bears S.18°W., 63 lks., mkd: ¼ S BT.

BLM dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #664, surveyed April 1968 - (DCSO records Vol. 34 Page(s) 14275)

Point for the ¼ sec. cor. of secs. 1 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:
T26S R2W
¼ S 1
 S 12
 1968

from which
A fir, 17" dia., bears N.72°E., 8 lks., mkd: ¼ S1 BT.
A fir, 13" dia., bears S.13°W., 47 lks., mkd: ¼ S12 BT.
Corner is located at the W edge of logged area.

Ken Hoffine - For: Lone Rock Timber Co. - 10/1999 - M 133-59

Found - 1958 BLM brass cap 0.2 ft. above ground.
23" D.Fir snag bears N.72½°E., 5.4 ft (rec. N.72°E. 5.26 ft.) well healed face & BLM location tag.
16" D.Fir snag bears S.12¾°W., 31.1 ft. (rec S.13°W. 31.02 ft.) well healed face & tag.
Corner lies with BLM reprod unit to South & West & is approx. 300 ft. Wes of rock road & 500 ft. North of rock road.