

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (Tsp. Cor.)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 10 Page(s) 4186)

 Set a Chinquapin post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 6, 31 and 36 and marked T26S S31 on NE.; R1W S6 on SE.; T27S S1 on SW.; R2W S36 on NW. faces, with 6 notches on N., S., E., and W. edges, from which
 A Laurel 7" dia., bears N.45°E., 28 lks. dist. mkd. T26S R1W S31 BT.
 A Fir 6" dia., bears S.60°E., 31 lks. dist. mkd. T27S R1W S31 BT.
 A Fir 40" dia., bears S.74°W., 25 lks. dist. mkd. T27S R2W S1 BT.
 A Fir 24" dia., bears N.3°W., 23 lks. dist. mkd. T26S R2W S36 BT.

Fd. and used corner in GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 12 Page(s) 4868-69)

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4785)

 The Cor. of Tps. 26 and 27 S., Rs. 1 and 2 W., which is a post greatly decayed and witnessed as described by the Surveyor General.
 In the place of the decayed stake, I set a basalt stone 15x12x8 ins., 10" in the ground for cor., marked with 6 notches on each edge.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 1967 - C.S. File 54/40-52

 Found - No trace of original corner stone or other obliterated BT.
 Orig. 40" now 48" Fir, down, S.74°W., 16.5 ft., open and shows scribe.
 Orig. 24" now down and almost completely buried Fir, N.3°W., 15.2 ft.
 Orig. 6" now 16" Fir, down, S.60°E., 20.5 ft., open and find obliterated blaze as called for.

Set Brass cap at cor. mkd: County Surveyors Office

| | | | |
|------|-----|------|-----|
| T26S | | S 36 | |
| T27S | R2W | S 1 | R1W |

1967

(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. for Sec. 36 (Tsp. Cor.)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

New BTs- 10" Cedar N.70°W., 36.5 ft. mkd. T26S R2W S36 CSBT
18" D.Fir S.88°W., 41.7 ft. mkd. T27S R2W S1 CS BT.
Corner lies on southerly slope.

Fd. BC & 2 BTs by D. Edwards, 3/2008 - M155-16