

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4152)

The west boundary of sec. 31 is 80.00 chs. Therefore at point midway on this line, 2.02½ chs. S of the ¼ sec. cor. on E. boundary of sec. 36, T.26S. R.2W., I establish ¼ sec. cor. on W. boundary of sec. 31, marked ¼ on E. face, from which:
A fir, 16 ins. dia., bears N.24°E., 44 lks., mkd: ¼ S31 BT
A cedar, 9 ins. dia., bears S.22°E., 44 lks., mkd: ¼ S31 BT.

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4280)

The ¼ cor. of sec. 31, T26S R1W, established by Deputy Mensch, which is a conglomerate stone, 12x8x6 ins., firmly set, marked and witnessed as described by the surveyor general, bears N.89°42'W., 74 lks. dist.
To this point, I now move the original stone, which I set 8" in the ground, for ¼ cor. of sec.31, marked ¼ on E. face; from which
A fir 18" dia., bears N.12°E., 56 lks. dist. mkd. ¼ S31 BT.
A Fir 30" dia., bears S.27°E., 19 lks. dist. mkd. ¼ S31 BT.
I destroy marks on bearing trees at former corner.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 10, 1967 - C.S. File 54/40-45

Found - Orig. Corner stone 12"x8"x6" in place mkd. "¼" on E. side.
Orig. 18" now 28" Fir, N.12°E., 37.0 ft., alive, shows good scar.
Orig. 30" now 40" Fir, S.27°E., 12.5 ft., alive, shows good scar.
Set Brass cap at cor. mkd: County Surveyors Office
T 26 S R 2 W | ¼ S 31 R1W
1967
Reset stone alongside in mound of stone.
This corner lies on steep southerly slope 87.8 ft. S. of ¼ of sec. 36, T26-2W. No new BTs marked.