

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4063)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner marked ¼ S on W. face, from which
A Fir 6" dia., bears N.10°E., 33 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.34°W., 12 lks. dist. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4091-92)

The ¼ sec. cor. is not found after careful search. Set temp. ¼ sec. cor.
Set a basalt stone 15x12x4 ins., 10" in the ground for ¼ sec. cor. on E. bdy. of sec. 36, T26S R2W, marked ¼ on W. face, from which
A Madrone 5" dia., bears S.61°W., 21 lks. dist. mkd. ¼ S36 BT.
A Madrone 5" dia., bears N.47°W., 20 lks. dist. mkd. ¼ S36 BT.

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4280)

(Midpoint) Set an iron post 3 ft. long, 1" dia., 26" in the ground for ¼ cor. of sec. 36, with brass cap mkd. ¼ S 36 |
1916

from which
A Fir 24" dia., bears S.87°W., 49 lks. dist. mkd. ¼ S36 BT
A Fir 30" dia., bears N.7°W., 23 lks. dist. mkd. ¼ S36 BT.
I destroy the corresponding cor. of the rejected revision survey and marks on bearing trees.
The cor. established by Deputy Mensch for the ¼ cor. of sec. 36, which is a basalt stone, 15x12x4 ins., firmly set, marked and witnessed as described by the surveyor general, bears N.43°15'W., 1.06 chs. dist. I now destroy this corner and marks on bearing trees.

Survey by Don Bentz - For: U.S. Forest Service - July 19, 1993 - C.S. File 63/153-13

Found - 1" Iron pipe, firmly set 10" above ground in a 2 ft. dia. mound of stone with a 2½" brass cap, properly mkd. (Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

50" D.Fir stump with healed blaze, bears N.7°W.,
15.3 ft.
41" D.Fir stump with healed blaze, bears S.87°W.,
32.3 ft.
New Accessories:
5" Fir with double blaze, upper scribed "¼ S36",
lower blaze scribed "BT" with nail and washer
stamped "LS 839" and bears S.41°W., 21.3 ft.
Set spike in center of 50" D.Fir stump which bears
N.7°W., 15.3 ft.
All BTs have a 6" red band painted around the trees and the
blaze face painted red. USFS sign 54-3, Bearing Tree, and
54-9, Land Surveying Monument, are nailed to all BTs.