

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4064-65)

Set Hemlock post 4 ft. long, 4" sq., 24" in the ground for corner to secs. 19, 24, 25 and 30 marked T26S S19 on NE.; R1W S30 on SE.; R2W S25 on SW. and S24 on NW. faces, with 4 notches on N. and 2 notches on S. edges, from which
A Fir 36" dia., bears N.20°E., 40 lks. dist. mkd. T26S R1W S19 BT.
A Cedar 20" dia., bears S.50°E., 20 lks. dist. mkd. T26S R1W S30 BT.
A Hemlock 10" dia., bears S.20°W., 47 lks. dist. mkd. T26S R2W S25 BT.
A Hemlock 18" dia., bears N.25°W., 34 lks. dist. mkd. T26S R2W S24 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4088) and 4090)

(Page 4088)
The cor. of secs.19, 24, 25 and 30 is not found after careful search. Set temp. sec. cor.
(Page 4090)
Point for cor. of secs. 24 and 25, T26S R2W falls on a basalt rock in place, 6x12x12 ins., above ground on which I cut a cross (X) at exact cor. point, with 4 notches on N. and 2 notches S. of cross, from which
A Fir 16" dia., bears S.18°W., 49 lks. dist. mkd. T26S R2W S25 BT.
A Fir 36" dia., bears N.38°W., 37 lks. dist. mkd. T26S R2W S24 BT.

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4283-84)

Intersect the original McQuinn cor. established in 1883 for the cor. of secs. 19, 24, 25 and 30, which point is now marked by a basalt stone, set at proper point as indicated by the bearing trees, which are as described by the surveyor general, except that the SW. and NW. bearing trees are dead and now unfit for further use.
I now perpetuate this cor. as the cor. of secs. 24 and 25 only, by setting, at exact cor. point, an Iron post, 3 ft. long, 3" dia., 24" in the ground, with brass cap marked:
(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T26S
— S 24
S 25
R2W
1916

from which

A Cedar 24" dia., bears S.74°W., 29 lks. dist. mkd. T26S R2W S25 BT.

A Fir 40" dia., bears N.7°W., 106 lks. dist. mkd. T26S R2W S24 BT.

I destroy marks on old bearing trees referring to secs. 19 and 30. I destroy the corresponding cor. of rejected revision survey and marks on bearing trees.

The cor. established by Deputy Mensch in 1910 as the cor. of secs. 24 & 25 (which is a Fir post, 4" sq., 12" above ground, properly marked and witnessed as described by the surveyor general, instead of a rock in place, as described in field notes) bears N.18°22'W., 2.47 chs. dist. I now destroy this cor. and marks on bearing trees.

Fd. OK, Feb. 1981 by G. Grubb - M 86-68

Don Bentz - For: U.S. Forest Service - July 19, 1993 - C.S. File 63/153-14

Found - 3" Iron pipe firmly set 8" above ground with a 3½" brass cap, properly marked.

31" Cedar bears S.74°W., 19.1 ft. with a partly healed lower blaze and an open upper blaze with no scribing.

40" D.Fir stump bears N.7°W., 70.0 ft. with healed blaze.

New BT - 8" W.Fir with upper blaze scribed "T26S R1W S30", lower blaze scribed "BT" with brass washer stamped "LS 839", bears S.21°E., 13.1 ft.

All BTs have a 6" red band painted around the tree and the blaze face painted red. USFS sign 54-3 "Bearing Tree" and 54-9 "Land Surveying Monument" are nailed to all BTs.