

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4285)

(43.30 chs.)
Top of bluff, 150 ft. high, bears NW. and SE. As true point for ¼ cor. of sec. 19 falls on bluff where a permanent cor. cannot be established, I therefore, at this point Set a basalt stone 14x10x6 ins., 10" in the ground, for witness cor. to the ¼ cor. of sec. 19, T26S R1W marked WC ¼ on E. face; from which
 A Fir 10" dia., bears N.70°E., 26 lks. dist. mkd. WC ¼ S19 BT.
 A Cedar 9" dia., bears S.24°E., 17 lks. dist. mkd. WC ¼ S19 BT.

(45.41 chs.)
True point for ¼ cor. of sec. 19 from which the old ¼ cor. sec. 19, established by Mensch, which is a basalt rock in place, marked and witnessed as described by the surveyor general, bears West, 64 lks. dist. I now destroy this cor. and marks on bearing trees.

George Grubb - For: U.S. Forest Service - Feb. 1981 - M 86-68

Found - Orig. 15" Cedar opened to find scribe marks "¼ S19" visible, bears S.24°E., 11.2 ft.
Set 2" x 30" I.P., 18" in the ground on solid rock, in a 3 ft. dia. x 2 ft. high mound of stone with a 3" brass cap mkd. "T26S R2W R1W 1981 LS 397 + 1/4 W.C. S19".
New BTs- A 7" Cedar bears S.22°E., 51.2 ft. scribed X BT.
 12" D.Fir bears N.41°E., 13.2 ft. scribed X BT.