

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700376

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T26-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4159)

-----

(65.17 chs.)

Left bank of Umpqua River, 2.50 chs. wide, course S.80°W. Point for closing cor. of secs. 18 & 19 will fall in river. On face of rock cliff 5 ft. above ground for witness cor. to the closing cor. of secs. 18 & 19, I cut a cross (X) at exact cor. point, WC CC on E.; with 3 grooves N. and S. of cross, from which

An Alder 5" dia., bears N.11°W., 29 lks. dist. mkd. WC T26S R1W S18 BT.

A Fir 10" dia., bears S.24°E., 16 lks. dist. mkd. WC T26S R1W S19 BT.

(77.00 chs.) (West)

Point for closing cor. of secs. 18 & 19 in river. (4.65 chs. S.1°20'E. of the cor. of secs. 13 & 24, T26S R2W.)

GLO Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4286)

-----

(Surveying along E. bdy. of sec. 24)

(86.56 chs.)

True point for closing cor. of secs. 18 & 19, falls in river. The witness cor. to this closing cor. established by Deputy Mensch in 1910, which is marked by a cross on face of rock bluff, witnessed as described by the surveyor general, bears East, 10.24 chs. dist.