

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4065-66)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 18, 19 and 24, marked T26S S18 on NE.; R1W S19 on SE.; R2W S24 on SW.; and S13 on NW. faces, with 3 notches on N. and S. edges, from which
A Fir 8" dia., bears N.45°E., 34 lks. dist. mkd. T26S R1W S18 BT.
A Fir 6" dia., bears S.15°E., 14 lks. dist. mkd. T26S R1W S19 BT.
A Fir 10" dia., bears S.14°W., 12 lks. dist. mkd. T26S R2W S24 BT.
A Fir 6" dia., bears N.60°W., 14 lks. dist. mkd. T26S R2W S13 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4087)

The cor. of secs. 13, 18, 19 and 24 bears West 55 lks. dist., no trace of the post is found. All the BTs are standing but are deeply overgrown.
I re-establish the cor. in its original position as the cor. of secs. 13 and 24, T26S R2W only, as follows:
Set a basalt stone 18x12x8 ins., 12" in the ground for cor. of secs. 13 & 24, marked with 3 notches on N. and S. edges, from which
A Fir 15" dia., bears S.14°W., 12 lks. dist. mkd. T26S R2W S24 BT.
A Fir 10" dia., bears N.60°W., 14 lks. dist. mkd. T26S R2W S13 BT.
Marks on former bearing trees referring to T26S R1W are sufficiently obliterated.

GL0 survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4263)

Found stone, firmly set, marked and witnessed as described by the surveyor general.

GL0 Survey by Fred Mensch, U.S. Surveyor Under Special Instructions dated May 25, 1916 - (DCSO records Vol. 10 Page(s) 4286)

(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Intersect the original McQuinn cor. established in 1883, as the cor. of secs. 13, 18, 19 and 24, and reestablished 1910 by Deputy Mensch as the cor. of secs. 13 & 24 only. This cor. is a basalt stone, 4x10x8 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - and crew - March 29, 1963 - C.S. File 52/77-12

Found - Pile of rocks at corner, chisel mark "--" on one of them.
20" Fir N.67°W., not N.60°W., 9.2 ft., cut open and found good scribing.
20" Fir S.27°W., not S.14°W., 7.9 ft., opened and found old face badly rotted. No scribing visible. This tree was opened approx. 50 yrs. ago & looked as if scrbg was chopped off at that time
No trace of original NE. and SE. trees.

Set Brass cap at cor. mkd: County Surveyors Office

T 26 S
R2W S 13 | R1W
S 24 |
1963

New BT - 9" D.Fir S.63°W., 11.4 ft. mkd. T26S R2W S24 CS BT.
Rescribe 20" D.Fir N.67°W., 9.2 ft. mkd. T26S R2W S13 CS BT.
Cor. lies approx. 130 ft. North of North Umpqua Highway.

Fd. OK, Feb. 1981 by G. Grubb - M 86-68

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 26, 1984 - C.S. File 62/21-9

Found - 1963 DCS0 brass disk on a 1" I.P. protruding 15" above ground in a 2 ft. dia. mound of stone. Cap properly mkd.
A 16"x10"x8" stone found with 3 notches possible on one edge. (1910 survey)
6" now a 23" D.Fir with a double well healed blaze, bears N.67°W., 9.2 ft. (Orig.)
10" now a 21" D.Fir with one chopped out and rotted blaze, no scribing visible and a double well healed blaze, bears S.27°W., 7.9 ft. (Orig.)
9" now a 10" D.Fir with a single well healed blaze, bears S.63°W., 11.4 ft. (1963 BT)

New BT - 8" Hemlock double blazed and scribed "T26S R2W S13 CS BT" bears N.9½°W., 16.5 ft.
Corner lies approx. 100 ft. N. of Hwy. 138 on a S. slope.

CONT.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011C

Fd. 2½" Brass dist stamped DOUGLAS COUNTY SURVEYORS OFFICE
stamped "T2S R1W R2W S13 S24 1990" (9-25-07)

N. 604371.651

E. 4290210.112

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2923, surveyed July 2018/March
2020- (DCSO records Vol. 59 Pages 24042)

At the cor. of secs. 13 and 24 only, reported by Mensch in
1916-18; perpetuated by Godfrey, in 1963; subsequently
perpetuated by Monrean, in November, 1984; monumented with an
iron post, 1" dia., firmly set, projecting 15" above ground,
in a mound of stone, 2 ft. base, 12" high, with a brass cap
(properly) mkd.

from which the remains of the BTs reported by Mensch

A fir snag, 23" dia., bears S.27¼°W., 7.9 ft., with no
marks visible on open decayed blaze. (Original)
(Record, S.14°W.)

A fir, 33" dia., bears N.71½°W., 9.2 ft., with a healed
blaze. (Original) (Record, N.60°W.)

and a bearing tree mkd. by Godfrey

A fir, 13" dia., bears S.60¾°W., 12.5 ft., with a healed
blaze.

and the remains of a bearing tree mkd. by Monrean

A roothole bears N.9¾°W., 15.9 ft., alongside of which is
a down hemlock, 12" dia., with a healed blaze.