

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4066)

-----  
Set Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner mkd. ¼ S. on W. face, from which  
    A Hemlock 10" dia., bears S.15°E., 19 lks. dist. mkd. ¼ S BT.  
    An Alder 20" dia., bears S.30°W., 25 lks. dist. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4086-87)

-----  
The ¼ sec. cor. bears E. 2.83 chs. dist. This cor. is a decayed post. The SE. BT is standing. I re-establish the cor. in its original position as the ¼ sec. cor. on E. bdy. of sec. 13, T26S R2W, marked ¼ on W. face, from which  
    A Cedar 24" dia., bears S.83°W., 52 lks. dist. ¼ S13 BT.  
    An Ash 10" dia., bears N.56°W., 48 lks. dist. mkd. ¼ S13 BT.  
I obliterate marks on former bearing tree referring to sec. 18.

Fd. Cor. OK, in GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4264)

Don E. Garrett - For: United States of America - Oct. 1972 - M 47-7

-----  
Set Brass cap marked "T26S R2W ¼ S13 1972 RPLS 544", from which  
    8" Fir bears S.2°W., 128.5 ft. scribed ¼ S13 BT.  
    6 ft steel fence post with U.S. Forest Service signs #'s 54-2 and 54-4, bears N.3°W., 5.0 ft.

Maurice E. Farr, LS #1181 - For: U.S. Forest Service - Jan. 13, 1984 - C.S. File 62/15-17

-----  
Found - 3" dia. brass cap firmly set, buried 4" in ground, properly mkd. set by Garrett in 1972.  
    13" D.Fir S.2°W., 128.5 ft. with healed double blaze.  
    A steel fence post, projecting 4 ft. above ground, N.3°W., 5.0 ft. with USFS signs #54-2 & 54-4 attached. (Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Corner for Sec. 13 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

New Accessories: (No suitable trees in S.13)  
A 6" D.Fir N.77°E., 116.5 ft. mkd. "X BT" on a single blaze.  
NE. corner of Butler's 2-story log house (approx. dimensions of 24 x 40 ft.) bears S.18½°W., 180.2 ft.  
Corner is 1 ft. East of 3'x6'x6' high boulder (recently moved to this location) and is 18 ft. E. of 30 ft. dia. pond. To locate, drive up USFS Rd. #4710-021 to gate, thence N. approx. 300 ft. to corner.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 3, 1992 - C.S. File 64/23-14

-----  
Found - 3" dia. brass cap 4" below ground.  
8" now 16" dia. D.Fir down and out of position (to be cut up) with a fully healed double blaze, root hole bears S.2°W., 128.5 ft. (agrees w/rec.)  
Steel fence post with U.S.F.S. sign, bears N.0½°E., 5.0 ft. (Rec. N.3°W., 5.0 ft.)  
6" now 9" dia. D.Fir with a fully healed single blaze, bears N.81°E., 116.5 ft. (Rec. N.77°E., 116.5 ft.)  
NE. corner of 2-story log cabin bears S.22½°W., 180.2 ft. (Rec. S.18½°W., 180.2 ft.)

New Accessories:  
3" dia. Holly tree, we did not blaze or scribe, in yard, bears S.14¼°W., 106.6 ft. No tags put on tree.  
12" dia. Willow tree, we did not blaze or scribe, in yard, bears N.5¼°E., 33.2 ft. No tags put on tree.  
SE. corner of old 20' x 20' log cabin bears N.25 3/4°W., 183.3 ft. Cabin not set on permanent foundation.  
Corner is 1 ft. E. of a 3'x6'x6' high boulder and 18' E. of a small pond. Cor. is at edge of yard. Owner did not want trees scribed. New BTs are only ones of their kind near cor.

Fd. ok by K. Hoffine, 6/2007 - M153-43

James M. Stanley, ODOT - Sept/Nov. 2007 - St. Hwy 138-011C

-----  
Fd disk stamped "RPLS 544 T26S ¼ S13 R2W R1W 1972" (10-16-07)  
N. 607034.677  
E. 4290346.653

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - For: Lone Rock Timber Management Co. - July 2010 - M161-10

-----  
Found - 1972 Garrett brass cap 0.4 feet below ground in bamboo thicket  
Steel fence post bears N.0½°E., 5.0 feet as per record  
17" Willow bears N.5¼°E., 33.2 ft as per record  
13" D.Fir bears N.81°E., 116.5 ft as per record  
Corner lies approx. 1.0 feet east of a 3'x6'x6' boulder and approx. 18 feet east of small pond.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24043-4)

-----  
The ¼ sec. cor. of sec. 13 only, reestablished by proportionate measurement by Garrett, in 1972; perpetuated by Farr, in 1984; subsequently perpetuated by Smith, in 1992. There is no remaining evidence of the original cor., therefore this point is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 2½" dia., firmly set, with top 4" below the surface of the ground, with a brass cap (properly) mkd.

from which a bearing tree mkd. by Farr  
A fir, 14" dia., bears N.80½°E., 116.5 ft., with a healed blaze.  
and a bearing tree mkd. by Smith  
A willow, 32" dia., bears N.1°W., 31.9 ft., no marks visible.  
and a new bearing tree  
A maple, 9" dia., bears S.37½°W., 25.2 ft., mkd. X BT on bark.

Corner is located in a bamboo thicket, E., 1.0 ft., of a boulder, 3x6x6 ft. A metal t-post is alongside the cor., with Forest Service signs Nos. 54-2 and 54-4 attached. Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument unless a similar marker was already in place.

Douglas Co. Surveyors Office - Crew: Jeff Lorsung- 7/2/2024 - C.S. File 67/58-22

-----  
Found - 3" brass cap (properly mkd) buried 4"  
continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Burned 14" Fir N.80½°E., 116.5 ft., healed blaze.  
32" willow N.1°W., 31.9 ft., no marks visible, add  
3½" mag nail right side center.  
A 9" maple S.37½°W., 25.2 ft., visible scribe X BT  
on bark, add 3½" mag nail right side center.  
A metal T-post is alongside the corner with USFF  
signs.

Note - Area burned 9/2020  
Compass decl. 14¼°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 172856.655 E 286511.854