

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700476

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only, T26-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4163)

Point for closing cor. of secs. 7 and 18 falls on a conglomerate rock in place, 4x10x12 ins., above ground on which I cut a cross (X) at exact cor. point, marked CC on E. with 2 grooves N. and 4 grooves S. of cross, from which
A Maple 5" dia., bears N.36°E., 26 lks. dist. mkd. T26S R1W S7 BT.
A Maple 5" dia., bears S.41½°E., 15 lks. dist. mkd. T26S R1W S18 BT.
(Point is 4.00 chs., S.4°8'E. of the cor. of secs. 12 & 13, T26S R2W)

Fd. and used in GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4264)

Don E. Garrett - For: United States of America - Oct. 1972
M 47-7

Set Brass cap mkd. "T26S S7 S18 R1W T26S R2 S13 1972 RPLS 544", from which
8" Fir bears N.52°E., 29.1 ft. scribed T26S R1W S7 BT.
7" Fir bears S.18½°E., 26.9 ft. scribed T26S R1W S18 BT.

Fd. OK by K. Hoffine, Oct. 1999 - M133-59

Ken Hoffine - For: Lone Rock Timber Management Co. - July 2010 - M161-10

Found - 1972 Garrett brass cap in mound of stones
14" D.Fir bears S.20½°E., 26.2 ft (record S.18½°E., 26.9 ft) healed face and tag.
12" D.Fir bears N.50¾°E., 29.4 ft (record N.52°E., 29.1 ft) healed face and tag.
Corner lies on steep rocky south facing slope.