

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4067)</p> <p>-----</p> <p>Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner mkd. ¼ S on W. face, from which A Fir 50" dia., bears N.70°E., 15 lks. dist. mkd. ¼ S BT. A Fir 70" dia., bears S.21°W., 40 lks. dist. mkd. ¼ S BT.</p>
<p>GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4085)</p> <p>-----</p> <p>No trace is found of the post but both BTs are standing and plainly marked. I re-establish the cor. in its original position as the ¼ sec. cor. on E. bdy. of sec. 12, T26S R2W, only as follows: Set a basalt stone 18x12x10 ins., 12" in the ground for ¼ sec. cor. marked ¼ on W. face, from which A Fir 70" dia., bears S.21°W., 40 lks. dist. mkd. ¼ S12 BT A Cedar 6" dia., bears N.77°W., 27 lks. dist. mkd. ¼ S12 BT. I obliterate marks on former bearing tree referring to sec 7</p>
<p>Fd. and tied in GL0 survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4265)</p>
<p>Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Clete Putnam, crew - April 17, 1961 - C.S. File 52/77-1</p> <p>-----</p> <p>Found - Rock at corner, no markings on rock, crumbly. Stump of 70" Fir S.21°W., 26.4 ft., no scribing. Cedar now 18", N.77°W., 17.8 ft. blaze still open, scribing visible "¼S". Tree still in good condition. Set Iron pipe with brass cap mkd: County Surveyors Office T 26 S R 2 W ¼ S12 1961 New BT - 12" D.Fir S.43°W., 61.0 ft. mkd. ¼ S12 CS BT.</p>
<p>Fd. OK and used in BLM resurvey by Lynn M. Roseberry, Cadastral Surveyor, under Group #664, Surveyed April 1968 - (DCSO records Vol. 34 Page(s) 14269-70)</p>
<p>Fd. OK by K. Hoffine, Oct. 1999 - M133-59</p>
<p>Cont.</p>

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ken Hoffine - For: Lone Rock Timber Management Co. - July 2010 - M161-10

Found - 1961 Douglas County brass cap in mound of stones
37" D.Fir bears S.41½°W., 60.7 ft (record S.43°W.,
61.2 ft Garrett map M47-7) healed face and tag.
24" cedar stump bears N.80°W., 18.0 ft (as per
Garrett map M47-7)
New BT - 18" D.Fir bears S.83½°W 18.7 ft we scribe T26S R2W
¼S 12BT and tag
Corner is 1.0 ft above ground and approx. 35 ft south & 80 ft
West of rock road. Put metal fence posts approx. 1.0 ft north
and South of corner.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 4/21/2022 (Filed 7/21/2022) - C.S. File 67/52-33

Found - DCS0 brass cap (properly mkd) in mound of stone
proj. 20", set deeper now proj. 8"
Burnt off, hollowed out, 38"x3½" D.Fir stump
S.41½°W., 60.7 ft.
Burnt stump 20"x4' Cedar N.80°W., 18.0 ft.
Burnt off stump 14"x6 ft. D.Fir S.83½°W., 18.7 ft.
Metal fence post approx. 1.0 ft. north and west.
New - 5/8" I.Rod inside 3/4" (I.D.)I.Pipe (26" long) proj
6" N.31½°W., 25.1 ft.
5/8" I.Rod inside 3/4" (I.D.)I.Pipe (26" long) proj
6" N.1°W., 65.7 ft.
Note - Corner is approx. 50' South & 30 ft West of Rock rd.
Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file
Lat: 43°19'18.23"N Long: 122°52'24.45"W