

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 10 Page(s) 4067-68)

-----  
Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 6, 7, and 12, marked T26S S6 on NE.; R1W S7 on SE.; R2W S12 on SW. and S1 on NW. faces, with 1 notch on N. and 5 notches on S. edges, from which  
A Fir 6" dia., bears N.55°E., 15 lks. dist. mkd. T26S R1W S6 BT.  
A Fir 6" dia., bears S.44°E., 135 lks. dist. mkd. T26S R1W S7 BT.  
A Fir 6" dia., bears S.46°W., 34 lks. dist. mkd. T26S R2W S12 BT.  
A Fir 4" dia., bears N.74°W., 21 lks. dist. mkd. T26S R2W S1 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4084)

-----  
The cor. of secs. 1, 6, 7 and 12, almost obliterated, only indistinct traces of BTs, being found. I re-establish this cor. in its original position as the cor. of secs. 1 and 12, T26S R2W only, as follows:  
A Fir 6" dia., for cor. of secs. 1 and 12, T26S R2W, I mark T26S S12 on SW.; and R2W S1 on NW. side, with 1 notch on N. and 5 notches on S. side, from which  
A Fir 36" dia., bears S.72°W., 44 lks. dist. mkd. T26S R2W S12 BT.  
A Fir 4" dia., bears N.33°W., 31 lks. dist. mkd. T26S R2W S1 BT.

Fd. and used in GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4265)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Clete Putnam, crew - April 17, 1961 - C.S. File 52/77-3

-----  
Found - 36" Fir S.72°W., 29 ft., uprooted and down, no scribing.  
Fir tree, now 12", N.33°W., 20.5 ft., showing good scar. Opened scar enough to see good scribing "B".  
All trace of Corner tree gone.  
Set Brass cap at cor. mkd:

(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>County Surveyors Office T 26 S R2W S 1 S12 1961</p> <p>New BT - 10" R.Cedar S.85°W., 8.4 ft. mkd. T26S R2W S12 CSBT Original NW. BT still in good condition.</p>
<p>Cor. Fd. OK and used in BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor, under Group #664, Surveyed April 1968 - (DCSO records Vol. 34 Page(s) 14270-71)</p>
<p>Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - April 17, 1987 - C.S. File 62/40-15</p> <p>-----</p> <p>Found - 1961 DCSO brass cap on a 1" I.P. surrounded by a small mound of stones, protrudes 12" above ground. Cap mkd. with 1/4. 4" now 15" dia. D.Fir with a fully healed single blaze, bears N.33°W., 21.5 ft. (agrees w/M 47-7; 1910 survey and Godfrey. Dist. is 20.5 ft.) Orig. BT. 36" now root hole with a tipped out 36" dia. D.Fir that has a fully healed single blaze, root hole bears S.72°W., 29.0 ft. (agrees w/rec) 1910 USFS witness post and sign bears South 5.3 ft., previously unrecorded, source unknown.</p> <p>We removed "1/4" from brass cap and build up a 2 ft. dia., 1 ft. high mound of stone. New BTs- 14" dia. R.Cedar double blazed and scribed "T26S R2W S1 CS BT", bears N.58°W., 26.2 ft. 4" dia. R.Cedar double blazed and scribed "X BT" bears S.48½°W., 31.2 ft.</p> <p>Corner lies at SE. corner of a new clear cut.</p>
<p>BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24044)</p> <p>-----</p> <p>The cor. of secs. 1 and 12 only, reported by Roseberry in 1968; perpetuated by Monrean, in 1987; monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, in a mound of stone, 3 ft. base, to the top, with a brass cap (properly) mkd. from which the remains of the BTs reported by Roseberry A roothole bears S.72°W., 29.0 ft., alongside of which is a down fir, 36" dia., no marks visible. (Original)</p> <p>continued next page</p>

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 17" dia., bears S.81½°W., 8.3 ft., with a healed blaze.  
A fir, 24" dia., bears N.33°W., 21.5 ft., with a healed blaze. (Original)  
and the bearing trees mkd. by Monrean  
A cedar, 5" dia., bears S.47½°W., 30.9 ft., with illegible scribe marks visible on partially healed blaze.  
A cedar, 24" dia., bears N.58¼°W., 26.5 ft., with a healed blaze.  
NAD 1983 (2011)  
Latitude: 43°19'44.94"N. Longitude: 122°52'25.58"W.