

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24045)

The ¼ sec. cor. of sec. 1 only, perpetuated by Godfrey, in 1961; from orig. evidence no longer in existence; monumented with an iron pipe, 1¼" dia., firmly set, projecting 12" above ground, in a collar of stone, with A brass cap (properly) mkd from which the remains of the bearing trees mkd. by Godfrey

A decayed living hemlock, 16" dia., bears N.35¾°E., 7.8 ft., with scribe marks E¼ S1 CS visible on partially healed blaze.

A hemlock snag, 13" dia., bears S.53¾°E., 11.5 ft., with scribe marks BT visible on partially healed blaze.

and new bearing trees

A fir, 13" dia., bears S.69¼°W., 33.2 ft., mkd. ¼ S1 BT.

A fir, 7" dia., bears N.52½°W., 15.5 ft., mkd. X BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle iron driven alongside each monument unless a similar marker was already in place.