

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Cor. Secs. 18, 19; 13 & 24 T26-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9630

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 18, 19, & 24, with brass cap mkd

T26S  
R2E|R3E  
S13|S18  
S24|S19  
1929

from which

- A fir, 30" dia., bears N.77°E., 79 lks., mkd: T26S R3E S18  
BT.
- A fir, 30" dia., bears S.51°E., 40 lks., mkd: T26S R3E S19  
BT.
- A fir, 24" dia., bears S.71°W., 71 lks., mkd: T26S R2E S24  
BT.
- A fir, 22" dia., bears N.30°W., 60 lks., mkd: T26S R2E S13  
BT.