

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7 (Witness Cor)

Alias 141600 Description Witness Cor. PLSS  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9818)

-----  
S89°55'E., on true line bet. secs. 6 & 7 at 38.80 chains  
True point for the ¼ sec. cor., falls in Boulder Creek, 50 lks wide, course SW  
At 39.95 chains  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for witness ¼ sec. cor., with brass cap marked

WC  
¼ S6  
S7  
1931

from which

A yew, 14" dia., bears N.28°E., 16 lks., mkd: WC ¼ S6 BT.  
A fir, 20" dia., bears S.24°W., 58 lks., mkd: WC ¼ S7 BT.