

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9806)

A fir, 8" dia., for the ¼ sec. cor., mkd:

¼ S 30 on W., and

S 29 on E sides

from which

A fir, 26" dia., bears S.69°E., 118 lks., mkd: ¼ S29 BT.

A fir, 16" dia., bears N.56°W., 37 lks., mkd: ¼ S30 BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - June 4, 1982 - C.S. File 61/36-21

Found - Orig. 8" fir, now 9" for ¼ corner. Good scar on east & west sides as per orig. notes. Tree is alive

Orig. 26" now 35" fir with good scar bears S.70½°E., 77.9 ft. (Rec. S.69°E.)

Orig. 16" now 18" fir with good scar bears N.60°W., 24.4 ft. (Rec. N.56°W.)

New - Set spike stamped "B01" in top of 30" fir stump bears N.44°W., 22.1 ft. (to spike)

Set spike stamped "B02" in top of 19" fir stump bears S.14½°W., 23.4 ft. (to spike).

Sketch and location map in C.S. file.