

TOWNSHIP 26 RANGE 3E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9806-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd:

|      |     |
|------|-----|
| T26S | R3E |
| S19  | S20 |
| S30  | S29 |
| 1930 |     |

from which

- A fir, 20" dia., bears N.21°E., 91 lks., mkd: T26S R3E S20 BT.
- A fir, 28" dia., bears S.62°E., 57 lks., mkd: T26S R3E S29 BT.
- A fir, 29" dia., bears S.60°W., 114 lks., mkd: T26S R3E S30 BT.
- A fir, 50" dia., bears N.77°W., 69 lks., mkd: T26S R3E S19 BT.