

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9816)

-----

Set an iron post, 3 ft. long, 2" dia., 5" in the ground to bedrock, and a mound of stone to top, for cor. of secs. 5, 6, 7, & 8, with brass cap mkd:

T26S | R3E  
S6 | S5  
S7 | S8  
1931

from which

- A fir, 10" dia., bears N.21°E., 31 lks., mkd: T26S R3E S5  
BT.
- A fir, 18" dia., bears S.75°E., 35 lks., mkd: T26S R3E S8  
BT.
- A fir, 20" dia., bears S.43°W., 84 lks., mkd: T26S R3E S7  
BT.
- A fir, 16" dia., bears N.75°W., 46 lks., mkd: T26S R3E S6  
BT.