

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION WC Cor. Secs. 5, 6; 31 & 32 T25½-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9744)

Point for cor. of secs. 5, 6, 31 & 32 falls on steep bare rock, impracticable to set cor.

N.0°04'W., 48 lks.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for witness cor., with brass cap mkd:

T25½S	R3E
<u>S31</u>	<u>S32</u>
S 6	S 5
W	C
T26S	
1931	

from which

A fir, 34" dia., bears N.13°E., 26 lks., mkd: WC T25½S R3E S32 BT.

A fir, 12" dia., bears S.10°E., 22 lks., mkd: WC T25½S R3E S32 BT.

A madrona, 6" dia., bears S.67°W., 44 lks., mkd: WC T25½S R3E S31 BT.

A fir, 7" dia., bears N.41°W., 42 lks., mkd: WC T25½S R3E S31 BT.