

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9789-90)

-----

Set an iron post, 3 ft. long, 2" dia., 6" in the ground, to bedrock, and in mound of stone to top, for cor. of secs. 28, 29, 32, & 33, with brass cap mkd:

T26S	R3E
S29	S28
S32	S33
1930	

from which

- A fir, 20" dia., bears N.33°E., 72 lks., mkd: T26S R3E S28 BT.
- A fir, 8" dia., bears S.28°E., 31 lks., mkd: T26S R3E S33 BT.
- A cross (X) on NE, face of rock 20x20x20 ft above ground bears S.57°W., 33 lks., mkd: X B O
- A pine, 24" dia., bears N.56°W., 173 lks., mkd: T26S R3E S29 BT.