

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9799)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S8|S9  
1931

from which

- A fir, 40" dia., bears S.21°E., 81 lks., mkd: 1/4 S9 BT.
- A fir, 20" dia., bears N.76°W., 49 lks., mkd: 1/4 S8 BT.

Kristian DeGroot, PLS 1941 - For: USFS - Crew Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-13

-----  
Found - 1" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2 1/2" brass cap properly stamped.  
GLO 1931

42" Fir bears S.38°E., 53.5 ft. w/healed blaze.  
(Rec. S.21°E.) 1931

30" Fir bears N.76°W., 32.3 ft. with a healed blaze.

New - I build a stone mound, 48" dia., base to top of monument and paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to BTs.