

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9799-800)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd:

T26S|R3E  
S5|S4  
S8|S9  
1930

from which

- A fir, 18" dia., bears N.61°E., 58 lks., mkd: T26S R3E S4  
BT.
- A fir, 6" dia., bears S.25°E., 79 lks., mkd: T26S R3E S9  
BT.
- A yew, 10" dia., bears S.81°W., 50 lks., mkd: T26S R3E S8  
BT.
- A yew, 8" dia., bears N.47°W., 71 lks., mkd: T26S R3E S5  
BT.