

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33, 34; 33 & 34 T27-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, W.S.C.E., under special instruction, dated Dec. 27, 1920, surveyed Aug. 1929/Aug 1930 - (DCSO records Vol. 24 Page(s) 10063)

-----  
Set an iron post, 3 ft. long, 2" dia., 34" in the ground, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd

T26S R3E  
S 33|S 34  
S 4|S 3  
T27S  
1930

from which

- A fir, 10" dia., bears N.57°E., 9 lks., mkd: T26S R3E S34 BT.
- A fir, 6" dia., bears S.9°E., 46 lks., mkd: T27S R3E S3 BT.
- A fir, 12" dia., bears S.39°W., 31 lks., mkd: T27S R3E S4 BT.
- A fir, 10" dia., bears N.30°W., 19 lks., mkd: T26S R3E S33 BT.