

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9776-7)

Set a basalt stone 24x11x8", 18" in the ground for cor. of secs. 27, 28, 33, & 34 mkd with 1 notches on S & 3 notch(es) on E edges and a cross on top, from which
A fir, 8" dia., bears N.36°E., 58 lks., mkd: T26S R3E S27 BT.
A fir, 8" dia., bears S.40°E., 55 lks., mkd: T26S R3E S34 BT.
A fir, 18" dia., bears S.12°W., 62 lks., mkd: T26S R3E S33 BT.
A cedar, 6" dia., bears N.67°W., 62 lks., mkd: T26S R3E S28 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, USFS & Deputy Co. Surveyor - Walter Barton, Dave Williams, & Joel Sheriff - May 12, 1977 - C.S. file 59/34-15

Found - Basalt stone 24"x11"x8", 6" above ground and firmly set in place. Marked with one notch on the South edge, three notches on the East edge and a "X" on top.
A 19" Cedar bears N.63°W., 41.7 ft. with healed blaze.
A 16" D.Fir bears N.36°E., 38.7 ft. with healed blaze.
A 28" D.Fir bears S.14°W., 41.2 ft. with healed blaze.
A 9" D.Fir stump bears S.43½°E., 35.8 ft. with healed blaze.
Set - 2½" Brass cap on 1" Gal. I.P. set 4" above ground surface and marked: County Surveyors Office T26S R3E S28 S27 S33 S34 1977.
New BTs- A 8" Hemlock bears S.11°E., 17.2 ft. scribed "T26S R3E S34 CS BT" on a double blaze.
Note - Corner lies 500 ft. East of F.S. Road No. 260 in a partial cut unit.