

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 15, 16, 21, & 22

Alias <u>403400</u>	Description <u>WC PLSS #</u>
Alias <u>                    </u>	Description <u>                    </u>
Alias <u>                    </u>	Description <u>                    </u>
Alias <u>                    </u>	Description <u>                    </u>

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9781-2)

-----  
N.0°02'W., bet. secs. 21 & 22 at 80.00 chains  
The true point for cor. of secs. 15, 16, 21, & 22, falls on steep bare rock;  
Thence S.89°51'E., 2.98 chains  
A fir, 36" dia., for witness cor. of secs. 15, 16, 21, & 22, mkd:

- T 26 S S 15 on NE
- R 3 E S 22 on SE
- W C S 21 on SW, and
- S 16 on NW sides,

from which

- A yew, 13" dia., bears N.51°E., 18 lks., mkd: WC T26S R3E S15 BT.
- A fir, 16" dia., bears S.38°E., 42 lks., mkd: WC T26S R3E S22 BT.
- A fir, 17" dia., bears S.45°W., 75 lks., mkd: WC T26S R3E S22 BT.
- A yew, 7" dia., bears N.75°W., 291 lks., mkd: WC T26S R3E S15 BT.