

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 9, 10, 15, & 16

Alias 400479 Description WC PLSS #
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9784)

N.0°02'W., bet. secs. 15 & 16 at 79.50 chains:
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd:

	W	C
T26S		R3E
S 9		S10
S16		S15
1930		

from which
A yew, 6" dia., bears N.9°E., 98 lks., mkd: WC T26S R3E S10 BT.
A fir, 56" dia., bears S.12°E., 55 lks., mkd: WC T26S R3E S15 BT.
A fir, 42" dia., bears S.54°W., 56 lks., mkd: WC T26S R3E S16 BT.
A hemlock, 10" dia., bears N.17°W., 60 lks., mkd: WC T26S R3E S9 BT.
At 80.00 chains
The true point for cor. falls near edge of Medicine Creek on insecure ground.