

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9786)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 9|S10
1930

from which

- A fir, 22" dia., bears N.44°E., 53 lks., mkd: 1/4 S10 BT.
- A fir, 30" dia., bears N.45°W., 46 lks., mkd: 1/4 S9 BT.

Douglas Co. Surveyors Office - Gary L. Langlitz - Mike Tompkins - Karen Cheney - Dec. 20, 1976 - C.S. File 59/26-25

Found - 1" iron pipe, loosely set and extending 16" above ground, brass cap attached. Cap is GLO set 1930. Cap marked erroneously 1/4 cor. secs. 3 and 10.

From which -

- Orig. BT 22" now 24" D.Fir, N.44°E., 35.0 ft. alive and well healed.
- Orig. BT 30" D.Fir, now a 34" snag, N.45°W., 30.4 ft. scribed "S9 BT" on unhealed face.

We reset the found monument 27" in the ground, and obliterate the erroneous markings on the cap. We re-stamp the monument to read as follows:

U. S. General Land Office Survey
T26S R3E
CS 1976
S9|S10
1/4
1930

Marked a new bearing tree - 16" D.Fir, S.77 1/2°W., 35.3 ft., scribed "1/4 S9 CS BT" on a double blaze.

Kristian DeGroot, PLS 1941 - For: USFS - Crew Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-14

Found - 1" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2 1/2" brass cap properly stamped. GLO 1930

- 26", fire killed, D.Fir snag bears N.44°E. 35.0 ft. w/healed blaze. 1930
- A root hole with burnt Fir remnants bears N.45°W., 30.4 ft. 1930
- 16" fire killed, D.Fir snag bears S.77°30'W., 35.5 ft. with a healed blaze. 1976 cont. next pg

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BOs- I build a stone mound, 48" dia. base to top of monument.

5/8"x30" iron rod, set 26" in the ground with plastic cap "BTS ENG-SURV" bears S.44°W., 20.0 ft. with a 6 ft. alum. post set alongside.

5/8"x30" iron rod, set 26" in the ground with plastic cap "BTS ENG-SURV" bears S.45°E., 20.0 ft. with a 6 ft. alum. post set alongside.

Paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to BTs.