

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9786)

A boulder, in place, 30x16x16", above ground for cor. of secs. 3, 4, 9, & 10 mkd with a cross (X) on top at exact point for cor., 5 notches on S, and 3 notches on E edges, from which

- A hemlock, 27" dia., bears N.21°E., 48 lks., mkd: T26S R3E S3 BT.
- A fir, 46" dia., bears S.31°E., 41 lks., mkd: T26S R3E S10 BT.
- A fir, 38" dia., bears S.79°W., 32 lks., mkd: T26S R3E S9 BT.
- A fir, 44" dia., bears N.29°W., 47 lks., mkd: T26S R3E S4 BT.

Kristian DeGroot, PLS 1941 - For: USFS - Crew Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-12

Found - The original 16"x16"x30" corner stone in place with an "X" chiseled on top, 5 notches on the south and 3 notches on the east edges. GLO 1931
37" Hemlock bears N.21°E., 31.7 ft. with a healed blaze.
50" Fir bears S.31°E., 27.1 ft. with a healed blaze.
47" Fir bears S.79°W., 21.1 ft. with a healed blaze.
53" Fir bears N.29°W., 31.0 ft. with a healed blaze.

Set - I remove the 16"x16"x30" corner stone and at the exact corner point I set a 2½"x30" alum. pipe, 8" in the ground in a 48" dia. mound of stone, base to top with a 3 ¼" alum. cap stamped:

U.S. DEPT. OF AGRICULTURE FOREST SERVICE
T26S R3E
S 4 | S 3
S 9 | S10
PLS 1941
1997

Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" continued next page signs to all BTs.