

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9764)

-----

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd:

T26S R3E  
S27 S26  
S34 S35  
1930

from which

- A fir, 24" dia., bears N.8°E., 78 lks., mkd: T26S R3E S26 BT.
- A pine, 36" dia., bears S.53°E., 42 lks., mkd: T26S R3E S35 BT.
- A cedar, 26" dia., bears S.56°W., 48 lks., mkd: T26S R3E S34 BT.
- A fir, 18" dia., bears N.82°W., 96 lks., mkd: T26S R3E S27 BT.