

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9771)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 10, 11, 14, & 15, with brass cap mkd:

T26S|R3E
S10|S11
S15|S14
1930

from which

- A pine, 32" dia., bears N.45°E., 53 lks., mkd: T26S R3E S11 BT.
- A pine, 30" dia., bears S.63°E., 44 lks., mkd: T26S R3E S14 BT.
- A pine, 30" dia., bears S.25°W., 54 lks., mkd: T26S R3E S15 BT.
- A pine, 32" dia., bears N.82°W., 20 lks., mkd: T26S R3E S10 BT.

Kristian DeGroot, PLS 1941 - For: USFS - Crew Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-16

Found - 2" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2½" brass cap properly stamped. GLO 1930

43" Pine bears N.45°E., 35.0 ft. with a healed blaze. GLO 1930

38" Pine bears S.63°E., 29.0 ft. with a healed blaze. GLO 1930

34" Pine bears N.82°W., 13.2 ft. with a healed blaze. GLO 1930

A root hole bears S.25°W., 35.6 ft. GLO 1930

New - 37" Pine bears S.77°W., 94.4 ft. scribed "T26S R3E S15 BT" with a brass washer stamped "PLS 1941" nailed into lower blaze.

Paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and " LAND SURVEY MONUMENT" signs to BTs.