

TOWNSHIP 26 RANGE 03E POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9773)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S10|S11
1930

from which

- A fir, 11" dia., bears S.32°E., 28 lks., mkd: 1/4 S11 BT.
- A fir, 9" dia., bears N.57°W., 28 lks., mkd: 1/4 S10 BT.

Kristian DeGroot, PLS 1941 - For: USFS - Crew Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-15

Found - 1" O.D. iron pipe, firmly set, projecting 10" above the ground with a 2 1/2" brass cap properly stamped.
GLO 1930

24" Fir bears S.32°E., 18.5 ft. with a healed blaze.
GLO 1930

New BT - 20" D.Fir bears N.72°W., 23.3 ft. scribed "1/4 S10 BT" with a brass washer stamped "PLS 1941" nailed into the lower blaze.

Paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and " LAND SURVEY MONUMENT" signs to BTs